



# Material Safety Data Sheet

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** 567-LINE CABOTS AQUADECK

**Recommended Use:** Surface coating. Applied by brush, roller or spray.

**Supplier:** Orica Woodcare  
**ABN:** 004 117 828  
**Street Address:** 1330 Ferntree Gully Road  
Scoresby 3179  
Australia  
**Telephone Number:** +61 3 9757 9570  
**Facsimile:** +61 3 9757 9590

**Emergency Telephone:** 1 800 033 111 (ALL HOURS)

## 2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of NOHSC; NON-HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

**Poisons** None allocated.  
**Schedule:**

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components / CAS Number	Proportion	Risk Phrases
Water	>60%	-
7732-18-5		
Synthetic polymer(s)	10-<30%	-
-		
Propylene glycol	1-<10%	-
57-55-6		
2-Butoxyethanol	<1%	R20/21/22, R36/38
111-76-2		
Ingredients determined not to be hazardous	to 100%	-
-		

## 4. FIRST AID MEASURES

**Product Name:** 567-LINE CABOTS AQUADECK  
**Substance No:** 000000021245

**Issued:** 03/05/2006

**Version:** 1



# Material Safety Data Sheet

- Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
- Skin Contact:** If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.
- Eye Contact:** If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.
- Ingestion:** Rinse mouth with water. If swallowed, give a glass of water to drink. Seek medical advice.
- Medical attention and special treatment:** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

- Hazards from combustion products:** Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes.
- Precautions for fire fighters and special protective equipment:** Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.
- Suitable Extinguishing Media:** Not combustible, however, if material is involved in a fire use: Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

## 6. ACCIDENTAL RELEASE MEASURES

- Emergency procedures:** If contamination of sewers or waterways has occurred advise local emergency services.
- Methods and materials for containment and clean up:** SMALL SPILLS: Collect in a container for disposal via special chemical waste collection. LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

- Conditions for safe storage:** Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

**Product Name:** 567-LINE CABOTS AQUADECK  
**Substance No:** 00000021245

**Issued:** 03/05/2006

**Version:** 1



# Material Safety Data Sheet

**Precautions for safe handling:** Keep out of reach of children. Avoid skin and eye contact.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

2-Butoxyethanol: 8hr TWA = 96.9 mg/m<sup>3</sup> (20 ppm), 15 min STEL = 242 mg/m<sup>3</sup> (50 ppm), Sk  
Propane-1,2-diol: total (vapour & particulates): 8hr TWA = 474 mg/m<sup>3</sup> (150 ppm)

As published by the National Occupational Health and Safety Commission.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

### Personal Protective Equipment:

Orica Personal Protection Guide No.1,1998: NOT IN USE

If there is a risk of eye contact, repeated or prolonged skin contact or inhalation wear gloves, safety glasses and a respirator. Always wash hands before smoking, eating, drinking or using the toilet.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Viscous liquid
<b>Colour:</b>	Clear Amber
<b>Odour:</b>	Ammoniacal
<b>Solubility:</b>	Miscible with water.
<b>Specific Gravity:</b>	1-1.1

**Product Name:** 567-LINE CABOTS AQUADECK  
**Substance No:** 000000021245

**Issued:** 03/05/2006

**Version:** 1



# Material Safety Data Sheet

Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	N App
Flammability Limits (%):	N App
Autoignition Temperature (°C):	N App
% Volatile by Weight:	N Av
Solubility in water (g/L):	Miscible
Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	100 (water)
Decomposition Point (°C):	N Av
pH:	8-9.5
Viscosity:	N Av
Evaporation Rate:	N Av

## 10. STABILITY AND REACTIVITY

<b>Chemical stability:</b>	Stable under normal conditions of use.
<b>Conditions to avoid:</b>	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
<b>Incompatible materials:</b>	Incompatible with oxidising agents.
<b>Hazardous decomposition products:</b>	Oxides of carbon.
<b>Hazardous reactions:</b>	None known.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	No adverse effects expected, however large amounts may cause nausea and vomiting.
<b>Eye contact:</b>	May be an eye irritant.
<b>Skin contact:</b>	Contact with skin may result in irritation. Component/s of this material can be absorbed through the skin with resultant toxic effects.
<b>Inhalation:</b>	Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea.

### Long Term Effects:

**Product Name:** 567-LINE CABOTS AQUADECK  
**Substance No:** 000000021245

**Issued:** 03/05/2006 **Version:** 1



# Material Safety Data Sheet

No information available for the product.

## Toxicological Data:

No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

**Disposal methods:** For large quantities: Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site. For small quantities: Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

**Classification:** Based on available information, not classified as hazardous according to criteria of NOHSC; NON-HAZARDOUS SUBSTANCE.  
**Poisons Schedule:** None allocated.

**Product Name:** 567-LINE CABOTS AQUADECK  
**Substance No:** 000000021245

**Issued:** 03/05/2006 **Version:** 1



# Material Safety Data Sheet

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

This material safety data sheet has been prepared by SH&E Shared Services, Orica.

### Reason(s) for Issue:

First Issue Primary MSDS

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

**Product Name:** 567-LINE CABOTS AQUADECK  
**Substance No:** 00000021245

**Issued:** 03/05/2006

**Version:** 1