



# Material Safety Data Sheet

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT

**Recommended Use:** Solvent based exterior timber stain. Applied by brush or roller.

**Supplier:** Orica Woodcare  
**ABN:** 004 117 828  
**Street Address:** 1330 Ferntree Gully Road  
Scoresby 3179  
Australia

**Telephone Number:** +61 3 9757 9570

**Facsimile:** +61 3 9757 9590

**Emergency Telephone:** 1 800 033 111 (ALL HOURS)

## 2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of NOHSC; HAZARDOUS SUBSTANCE.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

**Risk Phrases:** Flammable. May cause sensitisation by skin contact. Harmful: May cause lung damage if swallowed.

**Safety Phrases:** Keep out of the reach of children. Keep away from sources of ignition - No Smoking. Avoid contact with skin and eyes. Use only in well ventilated areas. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

**Poisons Schedule:** None allocated.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components / CAS Number	Proportion	Risk Phrases
Kerosine 8008-20-6	>60%	R38 R65
Pigments -	10-<30%	-
Synthetic polymer(s) -	10-<30%	-
White spirit (Stoddard solvent) 8052-41-3	10-<30%	R65

**Product Name:** 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT

**Substance No:** 000000010084

**Issued:** 24/07/2006

**Version:** 2



# Material Safety Data Sheet

2-octyl-2H-isothiazol-3-one 0.2% R23/24 R34 R22 R43 R50/53  
(Octhilinone)  
26530-20-1  
Ingredients determined not to be hazardous to 100%  
-  
-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764766) or a doctor.

**Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discoloration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

**Skin Contact:** If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

**Eye Contact:** If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** If swallowed, do NOT induce vomiting. Give a glass of water. Get to a doctor or hospital quickly.

**Medical attention and special treatment:** Treat symptomatically and as for exposure to hydrocarbon solvents.

## 5. FIRE FIGHTING MEASURES

**Hazards from combustion products:** Flammable liquid. On burning will emit toxic fumes, including those of oxides of carbon.

**Precautions for fire fighters and special protective equipment:** Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

**Suitable Extinguishing Media:** Foam, dry agent (carbon dioxide, dry chemical powder).

**Hazchem Code:** 3[Y]

**Product Name:** 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT  
**Substance No:** 000000010084

**Issued:** 24/07/2006

**Version:** 2



# Material Safety Data Sheet

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency procedures:** If contamination of sewers or waterways has occurred advise local emergency services.

**Methods and materials for containment and clean up:** SMALL SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wipe up with rag or absorbent paper.  
LARGE SPILLS: Shut off all possible sources of ignition. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

**Conditions for safe storage:** Store in a well ventilated area away from foodstuffs, oxidising agents and sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

**Precautions for safe handling:** Keep out of reach of children. Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

White spirits: 8hr TWA = 790 mg/m<sup>3</sup>

As published by the National Occupational Health and Safety Commission.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

**Product Name:** 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT  
**Substance No:** 000000010084

**Issued:** 24/07/2006

**Version:** 2



# Material Safety Data Sheet

## Engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

## Personal Protective Equipment:

Orica Personal Protection Guide No.1,1998: NOT IN USE

If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Always wash hands before smoking, eating, drinking or using the toilet.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Brown
Odour:	Solvent
Solubility:	Insoluble in water. Soluble in organic solvents.
Specific Gravity:	0.9 @20°C (approx.)
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	>23
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	N Av
Solubility in water (g/L):	Insoluble
Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	N Av
Decomposition Point (°C):	N Av
pH:	N App
Viscosity:	N Av
Evaporation Rate:	N Av

## 10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Oxides of carbon.

Product Name: 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT  
Substance No: 000000010084

Issued: 24/07/2006

Version: 2



# Material Safety Data Sheet

**Hazardous reactions:** None known.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs. Breathing in vomit may lead to aspiration pneumonia (inflammation of the lung).

**Eye contact:** May be an eye irritant.

**Skin contact:** Contact with skin may result in irritation. A skin sensitizer. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

**Inhalation:** Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

**Long Term Effects:**  
No information available for the product.

**Toxicological Data:**  
No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

**Disposal methods:** For large quantities: Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.  
For small quantities: Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

**Product Name:** 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT  
**Substance No:** 000000010084

**Issued:** 24/07/2006

**Version:** 2



# Material Safety Data Sheet

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

**UN No:** 1263  
**Class-primary:** 3 Flammable Liquid  
**Packing Group:** III  
**Proper Shipping Name:** PAINT

**Hazchem Code:** 3[Y]

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 1263  
**Class-primary:** 3 Flammable Liquid  
**Packing Group:** III  
**Proper Shipping Name:** PAINT

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN No:** 1263  
**Packing Group:** III  
**Proper Shipping Name:** PAINT

## 15. REGULATORY INFORMATION

**Classification:** This material is hazardous according to criteria of NOHSC; HAZARDOUS SUBSTANCE.

**Hazard Category:** Xn: Harmful  
Xi: Irritant

**Risk Phrase(s):** R10: Flammable.  
R43: May cause sensitisation by skin contact.

**Product Name:** 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT  
**Substance No:** 000000010084

**Issued:** 24/07/2006

**Version:** 2



# Material Safety Data Sheet

R65: Harmful: May cause lung damage if swallowed.

**Safety Phrase(s):** S2: Keep out of the reach of children.  
S16: Keep away from sources of ignition - No smoking.  
S24/25: Avoid contact with skin and eyes.  
S51: Use only in well ventilated areas.  
S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

**Poisons Schedule:** None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

This material safety data sheet has been prepared by SH&E Shared Services, Orica.

### Reason(s) for Issue:

5 Yearly Revised Primary MSDS  
Change in Hazardous Substance Classification  
Change in labelling requirements

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

**Product Name:** 861-LINE CABOTS TIMBER SHADES SEMI-TRANSPARENT  
**Substance No:** 000000010084

**Issued:** 24/07/2006

**Version:** 2