



Material Safety Data Sheet

Based on available information, not classified as hazardous according to criteria of NOHSC.
Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 550-LINE CABOTS KWIK STEP

Supplier: Orica Woodcare
ABN: 004 117 828
Street Address: 1330 Ferntree Gully Road
Scoresby 3179
Australia
Telephone Number: +61 3 9757 9570
Facsimile: +61 3 9757 9590

Emergency Telephone: 1 800 033 111 (ALL HOURS)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Product Description: Clear protective coating for timber floors. Applied by brush. Milky opaque liquid.

Components / CAS Number	Proportion	Risk Phrases
Water	>60%	-
7732-18-5		
Synthetic polymer(s)	10-<30%	-
-		
N-methyl-2-pyrrolidone	1-<10%	R36/38
872-50-4		
Dipropylene glycol monomethyl ether	1-<10%	-
34590-94-8		
2-Dimethylaminoethanol	1-<5%	R10, R20/21/22, R34, R41
108-01-0		
2-Butoxyethanol	<1%	R20/21/22, R36/38
111-76-2		
Additives	to 100%	-
-		

3. HAZARDS IDENTIFICATION

Poisons Schedule: None allocated.

Product Name: 550-LINE CABOTS KWIK STEP
Substance No: 00000007247

Issued: 01/08/2005 **Version:** 2



Material Safety Data Sheet

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764766) or a doctor.

- Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.
- Skin Contact:** If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.
- Eye Contact:** If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.
- Ingestion:** Rinse mouth with water. If swallowed, give a glass of water to drink. Seek medical advice.
- Notes to physician:** Treat symptomatically.

5. FIRE FIGHTING MEASURES

- Specific Hazards:** Non-combustible material.
- Fire-fighting advice:** Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.
- Suitable Extinguishing Media:** Not combustible, however, if material is involved in a fire use: Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

7. HANDLING AND STORAGE

- Handling advice:** Keep out of reach of children. Avoid skin and eye contact and breathing in vapour.
- Storage advice:** Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Product Name: 550-LINE CABOTS KWIK STEP
Substance No: 00000007247

Issued: 01/08/2005 **Version:** 2



Material Safety Data Sheet

No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

2-Butoxyethanol: 8hr TWA = 121 mg/m³ (25 ppm), Sk
Dimethylaminoethanol: 8hr TWA = 7.4 mg/m³ (2 ppm), 15 min STEL = 22 mg/m³ (6 ppm)
1-Methyl-2-pyrrolidone: 8hr TWA = 103 mg/m³ (25 ppm), 15 min STEL = 309 mg/m³ (75 ppm)

As published by the National Occupational Health and Safety Commission.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering Control Measures:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Keep containers closed when not in use.

Personal Protective Equipment:

Orica Personal Protection Guide No. 1, 1998: B - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, safety glasses and impervious gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Colour: Milky Opaque
Solubility: Miscible with water.
Specific Gravity: 1.06
Relative Vapour Density (air=1): >1

Product Name: 550-LINE CABOTS KWIK STEP
Substance No: 00000007247

Issued: 01/08/2005

Version: 2



Material Safety Data Sheet

Vapour Pressure (20 °C):	N Av
Flash Point (°C):	N App
Flammability Limits (%):	N App
Autoignition Temperature (°C):	N App
% Volatile by Weight:	N Av
Solubility in water (g/L):	Miscible
Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	100 (water)
Decomposition Point (°C):	N Av
pH:	8
Viscosity:	N Av
Evaporation Rate:	N Av

10. STABILITY AND REACTIVITY

Stability: No information available.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

- Ingestion:** No adverse effects expected, however large amounts may cause nausea and vomiting.
- Eye contact:** May be an eye irritant.
- Skin contact:** Contact with skin may result in irritation. Component/s of this material can be absorbed through the skin with resultant toxic effects.
- Inhalation:** Material may be irritant to the mucous membranes of the respiratory tract (airways). Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea.

Long Term Effects:
No information available for the product.

Toxicological Data:
No LD50 data available for the product.

12. ECOTOXICOLOGICAL INFORMATION

Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Product Name: 550-LINE CABOTS KWIK STEP
Substance No: 00000007247

Issued: 01/08/2005 **Version:** 2
Page 4 of 6



Material Safety Data Sheet

For large quantities: Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site. For small quantities: Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

Classification: Based on available information, not classified as hazardous according to criteria of NOHSC.

Poisons Schedule: None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

This material safety data sheet has been prepared by SH&E Shared Services, Orica.

Reason(s) for Issue:

Revised Primary MSDS

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot

Product Name: 550-LINE CABOTS KWIK STEP
Substance No: 00000007247

Issued: 01/08/2005

Version: 2



Material Safety Data Sheet

anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: 550-LINE CABOTS KWIK STEP
Substance No: 00000007247

Issued: 01/08/2005

Version: 2