ATTAR TEST REPORT NUMBER: 15/8779.1



The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards. Accredited for compliance with ISO/IEC 17025. Accreditation Number: 2735

25 March 2015

Total Pages: 2

Job No: M15/8779

WET PENDULUM SLIP RESISTANCE

Prepared for:	Cabot's Australia					
	1956 Princess Highway					
	CLAYTON VIC 3168					
Attention:	Keith Chu					
Test Site:	ATTAR, Unit 1, 64 Bridge Road, Keysborough.					
Test Date:	25 March 2015					
Test Specimens, Size &	1 coat x CFP Oil Based Satin, 1 coat x CFP Oil Based					
Quantity:	Satin with 5% Intergrain UltraGrip added, 1 coat x CFF					
	Oil Based Satin applied to MDF board, 600x1200 mm,					
			d. Refer to Figure 1.			
Sampling & Direction of Testing:						t
	applicable.					
Test Personnel:	Chris Peake					
Preparation:	Washed with water and pH neutral detergent, rinsed					
	with water, then dried.					
Fixed/Unfixed:	Unfixed					
Air Temperature:	23°C					
Test Equipment:	Munro Stanley Skid Resistance Tester (Pendulum)					
	Serial Number 0320, Calibrated 16/10/2013.					
Test Standard:	AS 4586: 2013 Slip resistance classification of new					
	pedestrian surface materials – Appendix A.					
Slider Rubber:	Slider 96 Batch No. #56 prepared on P400 & 3µm					
	lapping film.					
Classification Criteria:	Refer to Classification Criteria, attached as Appendix 1.					
	Specimen Number					SRV
British Pendulum Number	1	2	3	4	5	SKV
		40	47	46	17	47
	47	46	47	46	47	47

These results apply only to the specimens tested and it is recommended that before selection of flooring or paving materials the effect of service conditions, including maintenance procedures and wear on their slip-resistance be checked.

NOTE: Any specimens supplied will be disposed of in two (2) months time, unless otherwise instructed.

Marcus Braché

Senior Engineering Technician

Approved Signatory

This report may not be reproduced except in its entirety.

Page 1 of 2



ATTAR TEST REPORT NUMBER: 15/8779.1

25 March 2015 Total Pages: 2




Figure 1: Cabot's CFP Oil Based Satin with Ultragrip added to one coat.